



BLECH AL99.5 AW1050A H14/H24
EN573-3/EN485-1

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
0,8	4,400	6,800	
1,0	5,500	8,500	12,200
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
2,5	13,500	21,500	30,500
3,0	16,500	25,500	37,000
4,0	22,000	34,000	50,000
5,0	27,000	43,000	61,000




BLECH AL99.5 AW1050A H14/H24 EINSEITIG FOLIERT
EN573-3/EN485-1

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
3,0	16,500	25,500	37,000




BLECH AlMg1 AW5005 H14/H24 BANDELOX. E6/EV1
EINSEITIG FOLIERT

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
2	11,000	17,000	25,000




Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.


BLECH AIMg3 AW5754 H22


EN573-3/EN485-1

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,0	5,500	8,500	12,200
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
2,5	13,500	21,500	30,500
3,0	16,500	25,500	37,000
4,0	22,000	34,000	50,000
5,0	27,000	43,000	61,000


BLECH AIMg3 AW5754 H111

EN485-3/EN573-3

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
6,0	33,000	51,000	73,000
8,0	44,000	68,000	98,000
10,0	56,000	87,000	126,000


BLECH AIMg3 AW5754 H22 EINSEITIG FOLIERT


EN573-3/EN485-1

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,5	8,500	13,000	18,500
2,0	11,000	17,000	25,000
3,0	16,500	25,500	37,000

Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.


DUETT-WARZENBLECH AIMg3 AW5754
EN1386/EN573-3

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
1,5/2,0	9,000	14,000	20,000
2,5/4,0	15,500	24,000	34,500
3,5/5,0	21,000	32,500	47,000
5,0/6,5	29,000	45,000	65,000
8,0/9,5	46,000	71,000	102,000



QUINTETT-WARZENBLECH AIMg3 AW5754
EN1386/EN573-3

Stärke mm	1000 x 2000 mm kg/Tfl.	1250 x 2500 mm kg/Tfl.	1500 x 3000 mm kg/Tfl.
2,5/4,0	16,000	24,500	35,000
3,5/5,0	21,500	33,000	47,500
5,0/6,5	29,500	45,500	66,000



Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.